



MATRIXS DOUBLE SIDED ROUND LED DISPLAY

INDOOR

OUTDOOR



Cost effective, simple
and easy marketing on
digital signage displays!

Technical Specifications	P2	P2.5	P4	P4.68
Model Number	MTS-1R-3D-P2-ID	MTS-1R-5D-P2.5-ID	MTS-1R-6D-P4-OD	MTS-1R-6D-P4.68-OD
Pixel Pitch	2.0mm	2.5mm	4mm	4.68mm
Display side	Single/Double	Single/Double	Single/Double	Single/Double
LED Type	SMD2121	SMD2121	SMD2121	SMD2121
Pixel Density	250,000 Pixels/ m ²	160,000 Pixels/ m ²	111,111 Pixel/ m ²	62,500 Pixels/ m ²
Diameter	300mm	500mm	600mm	600mm
Brightness	800nits	800nits	1000nits	1000nits
Viewing Angle	H: 160°; V: 160°	H: 160°; V: 160°	H: 160°; V: 160°	H: 160°; V: 160°
Input Voltage	AC100-240V	AC100-240V	AC100-240V	AC100-240V
Max. Power	800W/ m ²	800W/ m ²	800W/ m ²	800W/ m ²
Ave. Power	280W/ m ²	280W/ m ²	280W/ m ²	280W/ m ²
Working Temperature	-20℃ ~ +50℃	-20℃ ~ +50℃	-20℃ ~ +50℃	-20℃ ~ +50℃
Working Humidity	10%-90%RH	10%-90%RH	10%-90%RH	10%-90%RH
Environment (option)	Indoor	Indoor	Indoor/outdoor	Indoor/outdoor
APPLICATION	Restaurants, Clinics, Hospitals, Hotels, Malls, Saloon, Spa, Gym, Pharmacy, Grocery, Super market, Buildings, Towers, Bar, Shops, Museums, Park, Government offices, Schools, Universities, Stadiums			